



Quality

The composition of the offer meets with the specifications of the European Standard EN 643.

Relevant grades are 1.02.00, 1.04.00, 1.05.00, and 4.01.00.

The maximum portion (by weight) of unwanted material is 3%.

According to the standard the term 'unwanted material' includes paper and board unsuitable for production. These at any rate comprise coated, and wet-strength finished papers not allowing dissolving in a standard production procedure.

Norske Skog reserves the right to refuse loads comprising more than five percent of weight of unwanted material.

Norske Skog reserves the right to downgrade loads comprising less than the portion of corrugated board given by EN 643.

Moisture content in paper and board for recycling

According to EN 643 the regular moisture content is 10% (o fair-dry weight).

Norske Skog reserves the right to deduct the difference between the actual percentage in a load and 10% from the total, if the actual percentage exceeds 11%.

Norske Skog reserves the right to refuse loads if their moisture content exceeds 16%.

Form of delivery

Delivery is in bales.

Bales have to feature a minimum weight of 450 kg. They have to be pressed and shaped in a way that stacking can be done safely.

Dimensions admissible are:

	minimum	maximum
Width	80 cm	130 cm
Height	70 cm	120 cm
Length	120 cm	220 cm

The size of the bales has to be uniform within a single load. Cross-wiring or double-wiring is not permitted. Wrapping, and plastic or steel strings are not allowed.

Deliveries come in tarpaulin-covered trucks. Walking-floor deliveries have to be agreed on in advance.